



Timber Resource Group



HARD MAPLE VENEER 9'6" + 10'6" lengths		
PP		18"+ butt logs, 4 clear faces, 1/3 heart, no defects
PRI		16"+17" butt logs, 4 clear faces, 1/3 heart, no defects
SEL		14"+15" butt logs, 4 clear faces, 1/3 heart, no defects
#1		12"+13" butt logs, 4 clear faces, 1/3 heart, no defects
#2		14"+, one 3" defect, 1/3 heart, 1 1/2" sweep, no rot or seams.
#3		12" +13", one 3" defect, 1/3 heart, 1 1/2" sweep, no rot or seams.

HARD MAPLE SAWLOGS 8', 10', 12', 14', 16' lengths		
SEL		14"+ 1/3 heart, 3 clear faces & better
#1		12"+ 1/3 heart, 3 clear faces & better
#2		10"+ 1/2 heart, 2 clear faces
#3 PAL		10"+ 1/2 heart, 1 clear face
PAL		8"+ straight & sound

RED OAK VENEER 9'6" + 10'6" lengths		
PP		19" + butt logs, 4 clear faces, no defects
PRI		16" to 18" butt logs, 4 clear faces no defects
SEL		14" + 15" butt logs only. 4 clear faces, no sweep
#1		13" 4 clear faces, no sweep
		14"+ up, 1 small defect, no sweep

RED OAK - BLACK OAK SAWLOGS 8', 10', 12', 14', 16' lengths		
SEL		14"+ 3 clear faces & better
#1		12"+ 3 clear faces & better
#2		10"+ 2 clear faces
#3 PAL		10" + 1 clear face
PAL		8"+ straight & sound

BEECH SAWLOG 8', 10', 12', 14', 16' lengths		
LR		12" + 2 clear faces & better, no diseased logs

MIXED HARDWOOD PALLET 8', 10', 12', 14', 16' lengths		
PAL		8"+ straight and sound
#3 PAL		18' only, 10"+, no sweep, no rot, no seams

ASH SAWLOGS 8', 10', 12', 14', 16' lengths		
SEL		14" + 3 clear faces & better
#1		12" + 3 clear faces & better
#2		10" + 2 clear faces
#3 PAL		10" + 1 clear face, 9" clean butt logs

ASH VENEER 8'6", 9'6" + 10'6" LENGTHS		
#1	N/B	12"-14", 1/3 heart, 4sc, straight. 15"+1/2 heart, 4sc, straight

BLACK CHERRY SAWLOG 8', 10', 12', 14', 16' lengths		
SEL		14" + 3 clear faces, no rot allowed
#1		12" + 3 clear faces
#2		10" + 2 clear faces
#3 PAL		10" + 1 clear face

RED MAPLE SAWLOGS 8', 10', 12', 14', 16' lengths		
SEL		14"+ 3 clear faces & better 1/3 heart
#1		12"+ 3 clear faces & better 1/3 heart
#2		10"+ 2 clear faces & better 1/2 heart
#3 PAL		10"+ 1/2 heart, 1 clear face

YELLOW / WHITE BIRCH VENEER 9'6" & 10'6" LENGTHS		
PRI		16"+ no defects
SEL		14"+ 15" no defects
#1		12"+ 13" clear, 14"+ one defect
#2		11" clear, 12"+13" one defect
#3		10" clear, 11" one defect
C-2		11"+ one defect, limited worm track allowed 9'6" & 10'6" only

YELLOW / WHITE BIRCH SAWLOGS 8', 10', 12', 14', 16' lengths		
SEL		14"+ 3 clear faces & better
#1		12"+ 3 clear faces & better
#2		10"+ 2 clear faces & better
BLT	XXXX	8"+ 2 clear faces & better. WB ONLY
#3 PAL		XXXX 10"+ 1 clear side. YB ONLY
PAL		XXXX 8"+ 1 clear face straight & sound. YB ONLY

SPRUCE & BALSAM FIR		
	SPRUCE	FIR
Logs Scaled		
Logs on Weight		
Treelength High Grade		

SPECIFICATIONS	
Sawlogs:	5" + up inside bark 12'-14'-16' with 4" trim
	16' lengths preferred; 6" max trim on 16' logs
	International 1/4" scale rule
SPRUCE & FIR TREE LENGTH HIGH GRADE SPECIFICATIONS	
7"	minimum butt diameter inside bark
5"	minimum top diameter inside bark
29'	minimum length; sorry, no "wheeler wood" 25' lengths
Any butt logs slashed out of over-length stems must be included in the run to be weighed and be cut to 16'4". Percentage of spruce loads must be at least 80% based on each week's deliveries unless previous arrangements have been agreed upon with Log Buyer. No rot allowed.	

POPLAR SAWLOGS 12',14',16' lengths		
SL		10"+ 6" trim 3 clear faces and better
PAL		10"+ logs not meeting above specs

HEMLOCK SAWLOGS 16' lengths		
LR	N/B	8"+ no ring shake (20% max 12' + 14' lengths)

*Hard Maple Birdseye, Hard Maple & Red Maple Curly
Sawlogs and Veneer Logs competitively priced individually.*

**EFFECTIVE DATE
JANUARY 2017**

YARDS

X Newport, ME

GENERAL SCALING NOTES AND ALLOWABLE DEFECTS

• All sawlogs must have 4"- 6" of trim. Poplar and Basswood not accepted as Hardwood Pallet logs. • All logs scaled using the International 1/4" scale rule. • All sawlogs and pallet logs scaled on even 2-foot increments from 8 thru 16 feet. • Rejected 9' veneer logs will be scaled as 9' sawlogs. • Logs not meeting specifications must be removed within two weeks or they will be disposed of. • All logs cut during the summer months must be trucked within two weeks, no stain accepted. • Straight seams are allowed with discount in sawlogs. • No chocolate heart, stain, ring or windshake accepted. • Burls, knots, rot, seams, splits, swells, excessive crook and sweep, surface checking, and end checking are all considered defects and will be scaled and graded as they affect the log. • Defects up to 3" in diameter are considered as one defect; defects larger than 3" are considered as two or more defects. **Please contact your log buyer for the current log prices delivered to the yard of a specific mill or if you have any questions. (Prices subject to change on short notice)**